



CX403

InTemp ????????

?????????????LCD?????????????

??GDP/GMP????????????????????/??

Important Information

???????????????? CX5001 ????????????? 100 ???30.5 ?????????????????

Supported Measurements

??

Features

- ????????????
- ??????????
- ?????????????????/????
- ??????????????? – ???????
- $\pm 0.5^{\circ}\text{C}$????????????
- ??GDP/GMP??
- ???????????????21 CFR Part 11???????
- ?????????????
- ????? CX Gateway ?????????????????
- ?????????????

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- 1-508-743-3309 (US & International)
- +45 6154 5745 (EMEA)

Technical Support (8am to 5pm ET, Monday through Friday)

- Email InTempHelp@onsetcomp.com
- Contact Support online www.onsetcomp.com/intemp/contact/support

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

InTemp ???????? (CX403) Specifications

???????	
??	-30°C ? 70°C (-22°F158???)
???	±0.5°C ?-15°?70°C (±0.9????5????158???) ±1.0°C ?-30°?-15°C (±1.8?????-22°?5°)
??	25°C??0.024°C (77?????0.04???)
???????????????	??NIST??

???	
?????	1???0?????
????	??30.5??100?????
???????	?????????????
?????????	-30°C ? 70°C (-22°F158???) 0?95%???????????
???????	1??18??
????	Two AAA batteries, user replaceable
???????	1 year, typical with logging interval of 1 minute. Faster logging intervals, remaining connected with the InTemp app, excessive report generation, numerous audible alarms, and paging all impact battery life.
??	128 KB (84,650 measurements, maximum)
?????????	Approximately 60 seconds; may take longer the farther the device is from the logger
??????	LCD is visible from 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range
??	9.4 × 4.5 × 2.59 ?? (3.7 × 1.77 × 1.02 ??)
??	90.2 ? (3.18 ??)
????	IP54

??	
----	--

??RTCA DO160G??21H??

