



MX2201

HOBO Pendant MX ???????

?????????

??HOBObconnect??Windows???

Important Information

????????????Windows????HOBObconnect????????????????HOBObconnect????????????Get cloud storage and access to the powerful tools of LI-COR Cloud® IoT software! (formerly HOBOLink) Add an MX Data Plan!



Compatible with
HOBObconnect® ?????

Supported Measurements

????, ??, ??

Features

- ??????????????????
- ??????
- ?????????96,000?????
- ?????30??100???
- ????????
- ??????????????
- LED?????????????????
- ?????HOBObconnect?????
- $\pm 0.5^{\circ}\text{C}$ $\pm 0.9^{\circ}\text{F}$???

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

HOBO Pendant MX ??????? (MX2201) Specifications

?????MX2201?MX2202?

??	???-20°C?70°C (-4°?158???????) ???-20°C?50°C (-4°?122?????????)
???	±0.5°C ?-20°?70°C (±0.9?????-4?????158???)
??	0.04??? (0.072???)
??	????0.1°C (??0.18???/?)
????	?????1/?(????????????????90%???????17??? ????????????90%????7???)

???? (MX2202)

??	0 ? 167,731 ??? (0?15,582???????)
????	??????? +10%??????????2???????

???

???????	-20°C ? 70°C ???? (???-4°158???)
??????	2G?? (0.07?? ??)
???	?30.5? (?100??)
?????	1 ?? (0 ????)
????	?30.5??? (?100????)
??????	???????????
??????	1??18??
????	?25°C???±1?? (?77???????±1??)
??	CR2032 3V ??????????
????	?25°C?77°F????????1????????????????????1?? ?25°C?77°F????????1????????????????????2?? ?? ????????????????????????????????
??	96,000 ???
???????	?45????????????????
????	?????EPDM O??
??	3.35 × 5.64 × 1.8 ?? (1.32 × 2.22 × 0.69 ??)
??	12.75 ? (0.45??)
????	IP68

