



CX405

InTemp ??????????RTD???

?????????????????LCD???

??GDP/GMP????????????????????/??COV

Important Information

????????????????? CX5001 ?????????????? 100 ???30.5 ??????????????????

Supported Measurements

??

Features

- ???NIST????????????????? • ??????????????????21 CFR Part 11????? • ?????????????????? • ?????????????????? •
- LCD?????????????????/????? • ?????????? • ?????AAA????????????? • ??FDA?USP????WHO?? •
- ??InTemp????????????????????????????InTempConnect????? • ???InTemp CX Gateway????????????????? ???????
- ??GDP?GMP?????????
- ???RTD??????????
- ??GDP/GMP??
- ?????????????

What's in the box

- InTemp CX405-RTD???????
- ??AAA 1.5V????
- ???????
- NIST?????

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- 1-508-743-3309 (US & International)
- +45 6154 5745 (EMEA)

Technical Support (8am to 5pm ET, Monday through Friday)

- Email InTempHelp@onsetcomp.com
- Contact Support online www.onsetcomp.com/intemp/contact/support

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

InTemp ??????????RTD??? (CX405) Specifications

??????	
??	-95°?50°C (-139°?122???)
???	±1.5°C??-95°?-40°C (±2.7?????-139°?-40???) ±1.0°C??-40°?-10°C? (±1.8?????-40°?14???) ±0.5°C?-10°C?50°C (±0.9?????-14°?122?????)
????????????????	??NIST??????
????	1.5? (4.92??)

????????	
??	-30°C?70°C (-22?????158???)
??	0.024°C?25°C? (77?????0.04???)
???	±0.5°C??-15°C?70°C (±0.9°C??5°F?158°F) ±1.0°C ?-30°?-15°C (±1.8?????-22?????5???)

???	
?????	1?? (0?????)
????	Approximately 30.5 m (100 ft) line-of-sight
??????	Bluetooth Low Energy (Bluetooth Smart)
????????	-30°C ? 70°C?0 ? 95% ?????????? (-22°?158?????0?95%???????????)
??????	1 second to 18 hours
????	Two AAA batteries, user replaceable
??????	1 year, typical with logging interval of 1 minute. Faster logging intervals, remaining connected with the app, excessive report generation, numerous audible alarms, and paging all impact battery life.