



CX1002

InTemp ????????????

??

???????WiFi?InTempConnect????????????????????????????????????

Important Information

CX1002 ? InTemp ?????? CX5001 ?????????????? InTempConnect
????????????????????????????/????????



Compatible with
????®

Supported Measurements

??

Features

What does it monitor?

<p>????????????????</p>

- ??USB-C????????????
- ?????????????????????????????
- ????????????? ?????????????????
- ?????????????????????
- ?????????????????????
- ??????LCD????????
- ?????????Wi-Fi????????
- ?????????CX1000????????????????IATA/FAA??
- InTempConnect????????????????????????????
- ??21 CFR?11??????
- ??????????????InTempConnect????????
- ??ISO17025/ILAC??????3????

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- 1-508-743-3309 (US & International)
- +45 6154 5745 (EMEA)

Technical Support (8am to 5pm ET, Monday through Friday)

- Email InTempHelp@onsetcomp.com
- Contact Support online www.onsetcomp.com/intemp/contact/support

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

InTemp ???????????? (CX1002) Specifications

Logger	
Type	Single use
Network Connectivity	CAT M1 (4G) with 2G Global Roaming WiFi SSID / Cell-ID 100m
Location / Accuracy	WiFi SSID / Cell-ID 100m
Memory	31,200 measurements
Data Recording Interval	Min. 5 Minutes up to max. 8 hours (Configurable)
Sending Interval	Min. 30 Minutes Or More (Configurable)
Total Runtime (Rec Duration)	30 days (@ Room Temperature) with 60 min data upload interval
Battery	3000 mAh, 3.7 Volts, 0.9g Lithium
Dimensions	100 x 50 x 18.5 mm (3.93 x 1.97 x 0.73 inches)
Weight	140 g (4.90 oz)
Environmental Rating	IP64

Temperature Sensor	
Range	-20° to 60°C (-68° to 140°F)
Accuracy	±0.5C from -20°C to 60°C (±0.9°F from -4°F to 140°F)
Resolution	0.1°C (0.32°F)

Notices	
Certifications	According To EN 12830, CE, BIS, FCC
Connection Interface	5V DC - USB Type C
????	Approved As Per AC91.21-ID, AMC CAT.GEN.MPA.140, IATA Guidance Document - Battery Powered Cargo Tracking Data Logger

